SINGLE PHASE 230 V / 50 Hz GASOLINE

ACCESS 2200 XL

Generator range

MAX OUTPUT 2.2 kW

VERY LONG
AUTONOMY

WELL EQUIPPED









The ACCESS 2200 XL gives you a maximum autonomy with a 15 liters extra-large fuel tank. Equipped as standard with an electronic Automatic Voltage Regulator, AVR, this generator is capable to power all your devices and utilities sensitive to voltage variations. User safety and equipment security is ensured by the differential earth leakage circuit breaker, in addition to the thermal overload protection for the sockets. The fully equipped electric control panel is easily accessible. This generator is ideal for construction site, leisure or emergency generator applications.

Serial equipment

- ✓ 4-stroke gasoline engine
- Recoil starter
- ✓ Electronic oil sensor security
- ✓ 2 Single phase socket 10/16 A Schuko
- ✓ Sockets protected by thermal circuit breaker
- ✓ Brushless alternator, 2 poles
- DC 12 V output 8.3 A + Voltmeter
- AVR: Automatic voltage regulator

Optional equipment

- → Wheelbarrow kit EXLE-ACCESS2200
- Kit interdif (factory option): Earth leakage circuit breaker
 30 mA + Copper Ground Rod + box

| | | ACCESS 2200 XL |
|---|-------|----------------------|
| Туре | | 1 phase |
| Voltage regulator | | AVR |
| Maximum AC output | kW | 2.2 |
| Continuous operating power (COP) | kW | 2 |
| Maximum Amps | А | 9.6 |
| AC voltage | V | 230 |
| Frequency | Hz | 50 |
| Noise power level CEE (LwA) | dB(A) | 95 |
| Noise power level @ 7 m | dB(A) | 70 |
| Engine | | WORMS R210 |
| Maximum output | HP | 5.4 |
| Fuel type | | Unleaded gasoline 95 |
| Fuel tank capacity | L | 15 |
| Autonomy (@ ¾ of the continuous output) | h | 12 h |
| Dimensions L x W x H | mm | 593 x 465 x 458 |
| Packaging dimensions L x W x H | mm | 610 x 490 x 500 |
| Dry weight | kg | 44.5 |
| Gross weight | kg | 46.5 |

WORMS Entreprises

ZAC de Lamirault 39 rue de Lamirault 77090 Collégien FRANCE

TEL. +33 (0) 1 64 76 29 50 FAX +33 (0) 1 64 76 29 99 www.wormsentreprises.com