# **Dynapac CC1000**







#### **Technical data**

Masses Masses	
Max. operating mass	1750 kg
Operating mass (incl. ROPS)	1685 kg
Module mass (front/rear)	790 kg/895 kg

Traction	
Speed range (Dual/TC/AS)	0-9 km/h
Vertical oscillation	±13°
Theor. gradeability	40 %

<b>**</b>	Compaction	
	Centrifugal force	17 kN
	Nominal amplitude	0.4 mm
	Static linear load (front/rear)	7.9/8.9 kg/cm
	Vibration frequency	70 Hz
	Water tank	110 I

Engine	
Manufacturer/Model	Kubota D1105-E4B T4f
Туре	Water cooled diesel
Rated power, SAE J1995	18 kW (24 hp ) @ 2800 rpm
Fuel tank capacity	23


Hydraulic	Hydraulic system		
Driving	Axial piston pump with variable displacement and servo. 2 radial piston motors with constant displacement.		
Vibration	Gear pump/motors with constant displacement.		
Steering	Gear pump with constant displacement.		
Service brake	Hydrostatic in forward and reverse lever.		
Parking/ Emergency brake	Failsafe brake in both drums.		

# **Dynapac CC1000**

### Double drum vibratory rollers



#### **Technical data**



Dimensions	
A. Wheelbase	1350 mm
B. Width	1070 mm
C. Curb clerance	465 mm
D. Drum diameter	584 mm
H2. Height, w/o ROPS/cab	1585 mm
K. Ground clearance	250 mm
L1. Length	2040 mm
L2. Length (ROPS)	2095 mm
O1. Overhang, right	35 mm
O2. Overhang, left	35 mm
R1. Turning radius, outside	2750 mm
S. Drum shell thickness	13 mm
W. Drum width	1000 mm
α. Steering angle	±34°

